

Pixel Collection

Acoustic Panels



The Pixel Collection evokes the notion that it is the minor details that come together to tell a bigger story. Comprised of a double-layer acoustic panel with subtle indented color highlights, Pixel panels are a vibrant design aesthetic for contemporary wall and ceiling applications.

The name "Pixel" is derived from the computer graphic term pixelation, which refers to the small dots of color required to give the final clear impression of an image. In the same way, the organised pattern of dots on Pixel panels creates an original, minimalist impression. Minimalism, balanced with the depth and texture of the circular cut outs, makes Pixel a holistic solution for both acoustics and aesthetics.


Thoughtfulness in the curation process means that each of the fifteen available colorways has been carefully selected to complement palettes of leading interior design. These colorways satisfy demands for both contrast and coordination, making this collection suitable for a variety of working, learning and living spaces.

Through a double-layer construction, Pixel panels achieve an enhanced acoustic performance rating, boasting a Noise Reduction Coefficient (NRC) of 0.60. Each panel in the double layer construction is also comprised of FilaSorb™, contributing to both the acoustic performance of the panel, as well as the smooth surface finish. FilaSorb™ is a substantially heterogeneous blend of fibers; different denier blended for specific acoustic performance.

In combination with other products in the Acoufelt range, the Pixel acoustic panel collection delivers a holistic and integrated Acoustic FWC™ solution – allowing architects and designers to use the floor, walls and the ceiling to absorb unwanted noise.









Wasabi + Marine


Pixel Design WM24






Midnight Blue + Butter

Pixel Design MT24





Metal + Slate







Carrot + Midnight Blue



Technical information

Acoustic NRC Rating Min. 0.60

Product Application | Wall and Ceiling

Dimensions 1,200mm x 2,400mm | 47"x 94"

Thickness 24mm +/- 10% | 0.94" +/- 10%

Weight 4800 g/m2 +/- 10% | 10.58 lb/ft2 +/- 10%

Material 100% Polyester

^{*}Acoufelt strives to fulfil the needs of their customers by producing the highest quality felt products. However due to the fine, fibrous and textural nature of the product, slight visual imperfections may be seen when viewing the product from less than 1 to 1.5 meters. These slight visual imperfections however, are within normal industry manufacturing tolerances. Allow for +/- 5mm Alignment Tolerance.

Environmental

Min. 60% recycled content including PET bottles

Low VOCs emission, formaldehyde and Phenol-free

ISO 105-B02 1994, 6-7

ISO 9705: 1993 Group 1
AS ISO 9705: 2003 Group 1
ASTM E84-17a Class A

Color Fastness

For warranty and installation guides, visit acoufelt.com



Superior breathability



Certified low VOC



Excellent resistance to fire



10 year lightfastness warranty



Super fine fibers to achieve a smooth surface appearance



3M Scotchgard protection



Thermal efficiency




Highly customizable



Anti-static treated – reducing dust cling

Sound Absorption Results



*Graph not to scale.

Frequency (Hz)	125	250	500	1000	2000	4000	NRC
as no air gap	0.02	0.57	0.41	0.58	0.87	0.85	0.60










Pearl + Carrot

Pixel Design PC24






Marine + Wasabi

Pixel Design MW24

Pixel Colourways







*Product specifications and information provided may change at any given time without notice.

**Simulations and photos are provided for visual impression purposes only. Actual products may differ to physical product due to printing and digital variations.

October 2019

